

Low Noise Amplifier DM-LNKU-40-101

Electrical Specifications (+25°C)

PARAMETER	UNITS
Frequency	15.1 to 15.35 GHz
Small Signal Gain	40 dB min
Flatness	±1.0 dB max
Noise Figure	1.4 dB max
P1dB	+10 dBm min
IP3	+20 dBm nom
VSWR (input/output)	1.4:1 nom
DC Power	+12 to +15 VDC, 160 mA nom
Max Input Power	+13 dBm CW

Mechanical Specifications

PARAMETER	UNITS
Size (L x W x H)	1.55" x 0.71" x 0.41"
Connectors (In/Out)	SMA female
Housing Material	Aluminum
Sealing	Hermetic
Cooling	External heatsink (not included)
Outline	001-0024

Features

Internal Voltage Regulator

Environmental Specifications (by design)

PARAMETER	UNITS
Operating Temperature	-55 to +85°C
Storage Temperature	-54 to +85°C
Relative Humidity	IAW MIL-STD-810F, up to 95%
Altitude	up to 30,000 ft
Shock	IAW MIL-STD-202G method 214, condition C

Classification

ECCN: EAR99

Test Data

Gain, Flatness, Noise Figure, P1dB, VSWR, DC Power at +25°C