

# Low Noise Amplifier DM-LNMB-30-103

## Electrical Specifications (+25°C)

PARAMETER	UNITS
Frequency	6.0 to 18.0 GHz
Small Signal Gain	30 dB min
Flatness	±2.0 dB max
Noise Figure	2.5 dB typ, 3 dB max
P1dB	+18 dBm min
VSWR (input/output)	2.2:1 nom
DC Power	+12 to +15 VDC, 275 mA nom
Max Input Power	+10 dBm CW

## Mechanical Specifications

PARAMETER	UNITS
Size (L x W x H)	0.998" x 0.75" x 0.365"
Connectors (In/Out)	SMA female
Housing Material	Aluminum
Sealing	Epoxy
Outline	001-0052

## Features

Internal Voltage Regulator  
Reverse Voltage Protection

## Environmental Specifications (by design)

PARAMETER	UNITS
Operating Temperature	-20 to +85°C
Storage Temperature	-20 to +85°C
Relative Humidity	IAW MIL-STD-810F, up to 95%
Altitude	up to 10,000 ft
Shock	IAW MIL-STD-202G method 214, condition C

## Classification

ECCN: EAR99

## Test Data

Gain, Flatness, Noise Figure, P1dB, VSWR, DC Power at +25°C