

Medium Power Amplifier DM-MPSC-18-102

Electrical Specifications (+25°C)

PARAMETER	UNITS
Frequency	2 to 6.5 GHz
Small Signal Gain	16 dB min
Flatness	±1 dB max
Noise Figure	5.6 dB max
P1dB	24 dBm min
IP3	34 dBm nom
VSWR (input/output)	1.8:1 nom
DC Power	+11 to 15+ VDC, 475mA nom
Max Input Power	+15 dBm CW

Mechanical Specifications

PARAMETER	UNITS
Size (L x W x H)	0.998" x 0.75" x 0.365"
Connectors (In/Out)	SMA (f)/SMA (f)
Sealing	Hermetic
Finish	Grey Paint, Mounting surface Ni finish
Marking	Black per MIL-STD-130
Outline	001-0052

Features

Internal Voltage Regulator
Reverse Voltage Protection

Environmental Specifications (by design)

PARAMETER	UNITS
Operating Temperature	-40 to +85°C
Storage Temperature	-54 to +85°C
Relative Humidity	IAW MIL-STD-810F, up to 95%
Altitude	up to 30,000 ft
Shock	IAW MIL-STD-202G method 214, condition C

Classification

ECCN: EAR99

Test Data

Gain, Flatness, Noise Figure, P1dB, VSWR, DC Power at +25°C