



Model Number C1805 Bandpass Filter

Rev. E
02/27/13

Features:

- Cavity Design
- Low Loss

Applications:

- Data Link
- Test Equipment

Package Size:

- 0.53" x 0.625" x 3.0"
- (Please see outline for exact dimensions)



Specifications: (+25° C)

-1 Passband	4400 to 4625 MHz
-1 Rejection	55 dB at 4250 and 4775 MHz
-2 Passband	4775 to 5000 MHz
-2 Rejection	55 dB at 4625 and 5150 MHz
-3 Passband	5250 to 5475 MHz
-3 Rejection	55 dB at 5100 and 5625 MHz
-4 Passband	5625 to 5850 MHz
-4 Rejection	55 dB at 5475 and 6000 MHz
Insertion Loss	1.5 dB Maximum
VSWR	1.5:1 Maximum
Connectors	SMA Female per MIL-C-39012



Delta Microwave

300 Del Norte Blvd. Phone: 805.751.1100 email: sales@deltamicrowave.com
Oxnard, CA. 93030 Fax: 805.240.9544 www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision letter upon order placement.

Written By	Approved By
------------	-------------