



Part Number DM-HPLS-160-101

GaN Power Amplifier

Rev. B
03/21/2016

Electrical Specifications (+25°C):

Frequency:	1 to 3 GHz
Small Signal Gain:	16 dB min
Gain Var. Over Temp	-0.02 dB/°C typical
Psat @ 35dBm Input:	1-2: 52; 2-3: 51 dBm min
Psat @ 35dBm Input:	160 W typical
Noise Figure:	9 dB max
DC Power:	45 VDC, 12.5 A nom at Psat
PAE:	25 % typical
VSWR (Input/Output):	1.8:1/2.0:1 nom
Harmonics:	-15 dBc typical @ Psat
Spurious:	-70 dBc typical
Input Power Handling:	40 dBm max
Mismatch Handling:	5.0:1 max
Operation:	CW

Features:

DC On/Off:	2 μ s; TTL Logic-Low "0V": ON; High "5V": OFF
Over Temp Shutdown:	at +90°C
Current Monitoring:	Included
Matching:	\pm 1.5 dB max; \pm 10° max
Temp and Current Monitoring	

Mechanical Specifications:

Size (L x W x H):	6.35" x 6" x 0.78"
Connectors (In/Out):	SMA (f)/N(f)
Sealing:	Hermetic
Finish:	Grey Paint, Mounting surface Ni finish
Marking:	Black per MIL-STD-130
Cooling:	External heatsink
Outline:	001-0070

Classification:

ECCN:	EAR99
-------	-------



Registered to AS9100 (with ISO 9001)

Delta Microwave

300 Del Norte Blvd.
Oxnard, CA. 93030

Phone: 805.751.1100
Fax: 805.240.9544

email: sales@deltamicrowave.com
www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision upon order placement.



Part Number DM-HPLS-160-101

GaN Power Amplifier

Rev. B
03/21/2016

Environmental Specifications (by design):

Operating Temperature:	-40 to +80°C
Storage Temperature:	-54 to +85°C
Relative Humidity:	IAW MIL-STD-810F, up to 95%
Altitude:	up to 30,000 ft
Vibration:	IAW MIL-STD-810F, Method 514.5, Table 514.5-I, Categories 12, 13, 14, 20
Shock:	IAW MIL-STD-202G method 214, condition C
Salt Fog:	5%, +35°C 96 hrs IAW MIL-STD- 810G method
Fungus:	IAW MIL-STD-810G method 508.6

Test Data:

Gain, Psat, VSWR, DC Power at +25°C



Delta Microwave

300 Del Norte Blvd.
Oxnard, CA. 93030

Phone: 805.751.1100
Fax: 805.240.9544

email: sales@deltamicrowave.com
www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision upon order placement.