



Part Number DM-HPX-100-103

GaN Power Amplifier

Rev 2
3/29/2016

Electrical Specifications (+25°C):

Frequency:	9.75 to 10.25 GHz
Small Signal Gain:	50 dB min
Gain Var. Over Temp	-0.05 dB/°C typical
Psat @ 5dBm Input:	50 dBm min
Psat @ 5dBm Input:	100 W typical
Noise Figure:	8 dB max
DC Power:	40 VDC, A nom at Psat
PAE:	30 % typical
VSWR (Input/Output):	2.0:1/1.5:1 nom
Harmonics:	-15 dBc typical @ Psat
Spurious:	-70 dBc typical
Input Power Handling:	15 dBm max
Mismatch Handling:	5.0:1 max
Operation:	Pulse, 100 μ s, 10% d.c.

Features:

DC On/Off:	1 μ s; TTL Logic-Low "0V": ON; High "5V": OFF
Over Temp Shutdown:	at +85°C
Current Monitoring:	Included

Mechanical Specifications:

Size (L x W x H):	3.6 x 3.4 x 0.67 inches
Connectors (In/Out):	SMA (f)/N (f)
Sealing:	Hermetic
Finish:	Grey Paint, Mounting surface Ni finish
Marking:	Black per MIL-STD-130
Cooling:	External heatsink

Classification:

ECCN:	3A001.b.4.b
-------	-------------



Delta Microwave

300 Del Norte Blvd.
Oxnard, CA. 93030

Phone: 805.751.1100
Fax: 805.240.9544

email: sales@deltamicrowave.com
www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision upon order placement.



Part Number DM-HPX-100-103

GaN Power Amplifier

Rev 2
3/29/2016

Environmental Specifications (by design):

Operating Temperature:	-40 to +70°C
Storage Temperature:	-54 to +85°C
Relative Humidity:	IAW MIL-STD-810F, up to 95%
Altitude:	up to 30,000 ft
Vibration:	IAW MIL-STD-810F, Method 514.5, Table 514.5-I,
Shock:	IAW MIL-STD-202G method 214, condition C
Salt Fog:	5%, +35°C 96 hrs IAW MIL-STD- 810G method
Fungus:	IAW MIL-STD-810G method 508.6

Test Data:

Gain, Psat, VSWR, DC Power at +25°C



Registered
to AS9100
(with ISO 9001)

Delta Microwave

300 Del Norte Blvd.
Oxnard, CA. 93030

Phone: 805.751.1100
Fax: 805.240.9544

email: sales@deltamicrowave.com
www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision upon order placement.