



Part Number DM-LNKU-45-101

Low Noise Amplifier

Rev 2
09/16/16

Electrical Specifications (+25°C):

Frequency	14.4 to 14.9 GHz
Small Signal Gain	45 dB min
Flatness	±1.0 dB max
Noise Figure	1.2 dB max
P1dB	+10 dBm min
IP3	+20 dBm nom
VSWR (input/output)	1.4:1 nom
DC Power	+12 to +15 VDC, 190 mA nom
Max Input Power	+13 dBm CW

Features:

Internal Voltage Regulator

Mechanical Specifications:

Size (L x W x H) inches	1.55 x 0.71 x 0.41
Connectors (In/Out)	SMA female
Housing Material	Aluminum
Sealing	Hermetic
Cooling	External heatsink (not included)
Outline	001-0024

Environmental Specifications (by design):

Operating Temperature	-40 to +85°C
Storage Temperature	-54 to +85°C
Relative humidity	IAW MIL-STD-810F, up to 95%
Altitude	up to 30,000 ft
Shock	IAW MIL-STD-202G method 214, condition C

Test Data:

Gain, Flatness, Noise Figure, P1dB, VSWR, DC Power at +25°C

Classification:

ECCN EAR99



Delta Microwave

300 Del Norte Blvd. Phone: 805.751.1100 email: sales@deltamicrowave.com
Oxnard, CA. 93030 Fax: 805.240.9544 www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision upon order placement.