



Model Number E1506 Bandpass Filter

Rev. D
02/28/13

Features:

- Cavity Design
- Low Loss

Applications:

- Communications
- Test Equipment

Package Size:

- 0.625" x 0.625" x 3.0"
(Please see outline for exact dimensions)

Weight:

- 1.5 oz., 0.1 lb.



Specifications: (+25° C)

Passband	19700 to 20200 MHz
Insertion Loss	1.5 dB Maximum
VSWR	1.5:1 Maximum
Passband Phase Deviation	$\pm 5^\circ$ Maximum
Rejection	40 dB at 18750 MHz 50 dB at 17300 MHz 30 dB at 24000 MHz 60 dB from 1 to 16000 MHz 60 dB from 26000 to 40000 MHz
Connectors	K Female
Operating Temperature	-40° to +50° C



Delta Microwave

300 Del Norte Blvd. Phone: 805.751.1100 email: sales@deltamicrowave.com
Oxnard, CA. 93030 Fax: 805.240.9544 www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision letter upon order placement.

Written By	Approved By
------------	-------------