



# Model Number Ku1521 Bandpass Filter

Rev. B  
03/07/13

## Features:

- Cavity Design
- Low Loss

## Applications:

- General
- Test Equipment

## Package Size:

- 0.43" x 0.64" x 2.21"

(Please see outline for exact dimensions)

## Weight:

- 1.11 oz., 0.07 lb.



## Specifications: (+25° C)

Passband	13900 to 14200 MHz
Passband Ripple	0.5 dB Maximum
Insertion Loss	1.7 dB Maximum
VSWR	1.8:1 Maximum
Rejection	65 dB from 300 KHz to 12400 MHz 65 dB from 15730 MHz to 18000 MHz
Input Power	27 dBm Maximum
Connectors	SMA Female per MIL-C-39012
Operating Temperatures	-20° to +50° C



## Delta Microwave

300 Del Norte Blvd. Phone: 805.751.1100 email: sales@deltamicrowave.com  
Oxnard, CA. 93030 Fax: 805.240.9544 www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision letter upon order placement.

Written By	Approved By
------------	-------------