



# Model Number Ku1936 Dual Bandpass Filter

Rev. B  
03/08/13

## Features:

- Cavity Design
- Low Loss

## Applications:

- SatCom

## Package Size:

- 0.75" x 1.5" x 4.0"

(Please see outline for exact dimensions)



## Specifications: (+25° C)

|                |  |
|----------------|--|
| Passband 1     | 12500 to 14800 MHz   |
| Passband 2     | 15850 to 16500 MHz   |
| Insertion Loss | 1.0 dB Maximum   |
| VSWR           | 1.5:1 Maximum  |
| Rejection      | 30 dB at 11700 MHz<br>30 dB at 15400 MHz<br>30 dB at 15600 MHz<br>30 dB at 17700 MHz |
| Connectors     | SMA Female In, SMA Male Out  |



## Delta Microwave

300 Del Norte Blvd. Phone: 805.751.1100 email: sales@deltamicrowave.com  
Oxnard, CA. 93030 Fax: 805.240.9544 www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision letter upon order placement.

Written By \_\_\_\_\_  
Approved By \_\_\_\_\_