



Model Number Ku5606 Diplexer

Rev. B
03/08/13

Features:

- Compact
- Light Weight
- Optional Solder Pin Interface
- High Power
- Low Loss

Applications:

- Tactical Common Data Link (TCDL)
- Test Equipment

Package Size:

- 0.4" x 1.4" x 2.1"
(Please see outline for exact dimensions)



Specifications: (+25° C)	Channel 1	Channel 2
Passband	14400 to 14830 MHz	15150 to 15350 MHz
Insertion Loss	1.5 dB Maximum	1.5 dB Maximum
VSWR	1.5:1 Maximum	1.5:1 Maximum
Rejection	40 dB from 15150 to 15350 MHz	40 dB from 14400 to 14830 MHz
Power Handling	5 Watts	5 Watts
Connectors	SMA Female per MIL-C-39012 Optional Solder Pins	
Operating Temperature	-40° to +70° C	



Delta Microwave

300 Del Norte Blvd. Phone: 805.751.1100 email: sales@deltamicrowave.com
Oxnard, CA. 93030 Fax: 805.240.9544 www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision letter upon order placement.

Written By	Approved By