



# Model Number Ku5917 Diplexer

Rev. B  
03/08/13

## Features:

- Folded Waveguide Design
- Integrated Coupler
- Low Loss

## Applications:


- Tactical Common Data Link (TCDL)
- Test Equipment

## Package Size:

- 0.9" x 3.1" x 6.25"  
(Please see outline for exact dimensions)

## Weight:

- 5.23 oz., 0.33 lb.



Specifications: (+25° C)	Channel 1	Channel 2
Passband	14530 to 14930 MHz	15150 to 15350 MHz
Insertion Loss	1.7 dB Maximum	1.8 dB Maximum
VSWR	1.5:1 Maximum	1.5:1 Maximum
Rejection	60 dB from 12400 to 14260 MHz 95 dB from 15130 to 15370 MHz 60 dB from 15370 to 18000 MHz 45 dB from 29060 to 29830 MHz	60 dB from 12400 to 14519 MHz 95 dB from 14520 to 14940 MHz 60 dB from 15630 to 18000 MHz 45 dB from 30300 to 30700 MHz
Coupling	30 ± 2 dB	
Directivity	12 dB	
Power Handling	25 Watts	25 Watts
Connectors	SMA Female per MIL-C-39012	



## Delta Microwave

300 Del Norte Blvd. Phone: 805.751.1100 email: sales@deltamicrowave.com  
Oxnard, CA. 93030 Fax: 805.240.9544 www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision letter upon order placement.

Written By \_\_\_\_\_ Approved By \_\_\_\_\_