



Model Number L59106

7 Channel GPS Filter/Amplifier

Rev -
3/7/05



- 7 Matched Channels
- Anti-Jam Receiver Applications
- L1 and L2 Independent Operation*
- Low Noise Figure
- Cavity Filter
- Discreet Amplifier
- Excellent out-of-band attenuation

Applications:

- Aircraft
- Maritime
- Mobile
- Test Equipment

Package size:

- 1.6 x 2.72 x 8.44

(Please see outline for exact dimensions)

Center Frequencies	1227.6 and 1575.42 MHz
Gain	+22 - +26 dB
Passband Ripple	0.5 dB maximum
Passband Bandwidth	± 18 MHz minimum
-60 dB Bandwidth	± 100 MHz maximum
-75 dB Bandwidth	± 175 MHz maximum
Rejection	-75 dB from 1-40,000 MHz
Input VSWR	1.5:1 maximum
Output VSWR	1.6:1 maximum
Gain Matching channel to channel	2.0 dB maximum
Group Delay Matching channel to channel	+/- 1 ns max at center
RF Input Power	+55 dBm in-band pulsed (Survive) +65 dBm out-of-band pulsed (operate)
Noise Figure	3.0 dBm maximum @ 25C
1dB compression point	+12 dBm minimum
Output Power	+19 dBm Maximum
Output Protection	Unit must be stable under any load without damage
Power Requirements (Via RF output connectors)	3.8 - 5.5 VDC @ 1.4 amps maximum 1.1 amp Typical
Noise Diodes (output)	+12 dBm minimum rise when activated
Noise (input)	Via SMA female external connector. (Connected to channel 1 with a 17 dB coupler to antenna)
Connectors (Input)	6 SMA Female, 1 SMA Male
Connectors (Output)	7 SMA Female
Size	See Outline
Temperature	-40° C to +85° C Operating

*L1 and L2 have independent filtering, diode protection, and LNA.



Delta Microwave

1301 Vanguard Dr.
Oxnard, CA. 93033

Phone: 805.240.1044
Fax: 805.240.9544

email: sales@deltamicrowave.com
www.deltamicrowave.com

--	--

By _____ Checked _____

Delta Microwave reserves the right to change specifications without notice. Please verify specification revision letter upon order placement.