



# Model Number L5990

## GPS Dual filter with DC Bypass

Rev.B  
06/19/14



### Features:

- Cavity Design
- Low Loss
- DC Bypass

### Applications:

- Maritime
- Airborne
- Mobile
- Timing
- Test Equipment

### Package size:

- 2.0 x 2.5 x 6.0"

(Please see outline for exact dimensions)

Parameter	L1	L2
Center Frequency	1575.4 MHz	1227.6 MHz
1 dB Bandwidth	$\pm 10$ MHz min	$\pm 10$ MHz min
3 dB Bandwidth	$\pm 20$ MHz max	$\pm 20$ MHz max
50 dB Bandwidth	$\pm 55$ MHz max	$\pm 55$ MHz max
VSWR	1.5:1 @ $f_0$	
Loss	1.2 dB max	
Ultimate Rejection	80 dB minimum for all frequencies Between 100 MHz and 3.5 GHz that are Greater than $\pm 100$ MHz from L1 and L2.	
DC Bypass	Thru RF Connectors	
Continuous Operating Temperature	- 54° C to + 71° C	
Elevated Temperature	+71° to +95° C	
Non Operating Temperature	-62° to +95° C	
Altitude	-1000 to +55,000 feet	
Humidity	100 percent, condensing	
Sand and Dust	MIL-STD-810, Method 510.1, Procedure I.	
Salt Spray	MIL-STD-810, Method 510.1, Procedure I	
Salt Water Immersion	Non-operating, One-hour immersion per MIL-STD-810, Method 512.1, Procedure III.	
Shock	MIL-STD-810, Test Method 516.2, Procedure I Amplitude @ 20 g and time 11 ms	
Rain	MIL-STD-810, Test Method 506.1, Procedure I	
Reliability (MTBF)	193,000 hours per MIL-HDBK-217 for Airborne, Uninhabited, Fighter Environment	
Finish	Haze Gray per MIL-P-24441, Type 1	
RF Connectors	Type "N" Female	
Size	See Outline Drawing	



## Delta Microwave

300 Del Norte Blvd.  
Oxnard, CA. 93030

Phone: 805.751.1100  
Fax: 805.240.9544

email: sales@deltamicrowave.com  
www.deltamicrowave.com

--	--

By \_\_\_\_\_ Checked \_\_\_\_\_