



# Model Number E1508 Bandpass Filter

Rev. D  
02/28/13

## Features:

- Cavity Design
- Low Loss

## Applications:

- Communications
- Test Equipment

## Package Size:

- 0.5" x 0.5" x 2.5"  
(Please see outline for exact dimensions)

## Weight:

- 1.3 oz., 0.1 lb.



## Specifications: (+25° C)

Passband	29574 to 29990 MHz
Insertion Loss	1.5 dB Maximum
VSWR	1.5:1 Maximum
Passband Phase Deviation	± 5° Maximum
Rejection	40 dB at 29388 MHz 40 dB at 30356 MHz 60 dB from 1 to 29000 MHz 60 dB from 30500 to 40000 MHz
Connectors	K Female
Operating Temperature	-40° to +50° C



## Delta Microwave

300 Del Norte Blvd. Phone: 805.751.1100 email: sales@deltamicrowave.com  
Oxnard, CA. 93030 Fax: 805.240.9544 www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision letter upon order placement.

Written By	Approved By
------------	-------------