



Model Number E1911

Space Qualified Bandpass Filter

Rev. F
03/06/13

Features:

- Cavity Design
- Low Loss

Applications:

- Communications
- Test Equipment

Package Size:

- 0.51" x 0.966" x 1.5"
(Please see outline for exact dimensions)

Weight:

- 0.54 oz., 0.03 lb.



Specifications: (+25C)

Passband	19700 to 20200 MHz
Insertion Loss at Ambient	2.0 dB Maximum
Insertion Loss Variation Over Temperature	0.4 dB Maximum
Flatness Over 500 MHz	0.4 dB Maximum
Flatness Variation Over Temperature	0.1 dB Maximum
Gain Slope	0.015 dB/MHz Maximum
Group Delay Variation Over any 500 MHz	1.5 ns Maximum
Return Loss	20 dB Minimum
Rejection	15 dB below 19600 MHz 35 dB below 19500 MHz 50 dB at 30000 MHz
Connectors	SMA / SMP
Operating Temperature	-15° to +76° C



Delta Microwave

300 Del Norte Blvd. Phone: 805.751.1100 email: sales@deltamicrowave.com
Oxnard, CA. 93030 Fax: 805.240.9544 www.deltamicrowave.com

Delta Microwave's Quality Management System has been assessed by NSF-ISR and found to be in conformance with AS9100:2009, Rev. C. Delta Microwave reserves the right to change specifications without notice. Please verify specification revision letter upon order placement.

Written By	Approved By
------------	-------------